

## 20W LED防水型

- 接綫:20cm綫材
- L, N: AC輸入
- V黑: DC輸出負端
- +V紅: DC輸出正端

輸入電壓範圍

AC input voltage range

170~264VAC 47~63Hz

輸入電流

Input current

0.28A/230V

衝擊電流

AC inrush current

冷啓動電流 30A/230V

Cold-start current 30A/230V

漏電電流

Leakage current

<0.5mA/240VAC

過載保護

Over load protection

105~150% 切斷輸出,自動恢復

105~150% hiccup mode, auto-recovery

防水等級

Water level

IP68

啓動、上升、保持時間

Setup rise hold up time

200ms 100ms 30ms

耐壓性

Withstand voltage

I/P-O/P:3KvAC 1 minute

I/P-FG:1.5KvAC 1 minute

O/P-FG:0.5KvAC 1 minute

工作溫度、濕度

Working temperature

0~40℃@100%put

-10℃@80%put

50℃@60%put

重量/包裝

Weight/packing

0.2kg,80pcs/16kg

型號Type

輸出Output

差值Error

範圍range

效率Efficiency

FS-20-12

12V, 2.1A

±1%

50mV

76%

FS-20-15

15V, 1.6A

±1%

100mV

77%

FS-20-24

24V, 1.0A

±1%

100mV

80%