

30W LED防水型



- ☒ 接綫:20cm綫材
- 田 L, N: AC輸入
- 田 -V黑: DC輸出負端
- 田 +V紅: DC輸出正端

輸入電壓範圍 AC input voltage range	170~264VAC 47~63Hz
輸入電流 Input current	0.42A/230V
衝擊電流 AC inrush current	冷啓動電流 36A/230V Cold-start current 36A/230V
漏電電流 Leakage current	<2mA/240VAC
過載保護 Over load protection	105~150% 切斷輸出,自動恢復 105~150% hiccup mode, auto-recovery
防水等級 Water level	IP68
啓動、上升、保持時間 Setup rise hold up time	200ms 100ms 30ms
耐壓性 Withstand voltage	I/P-O/P:1.5KvAC 1 minute I/P-FG:1.5KvAC 1 minute O/P-FG:0.5KvAC 1 minute
工作溫度、濕度 Working temperature	0~40℃@100%put -10℃@80%put 50℃@60%put
重量/包裝 Weight/packing	0.25kg,80pcs/20kg

型號Type	輸出Output	差值Error	範圍range	效率Efficiency
FS-30-12	12V,0~2.1A	±1%	100mV	76%
FS-30-15	15V,0~1.6A	±1%	100mV	78%
FS-30-24	24V,0~1.0A	±1%	100mV	78%