

50W LED防水型



- ☒ 接綫:20cm綫材
- 田 L, N: AC輸入
- 田 -V黑: DC輸出負端
- 田 +V紅: DC輸出正端

輸入電壓範圍
AC input voltage range

170~264VAC 47~63Hz

輸入電流
Input current

0.62A/230V

衝擊電流
AC inrush current

冷啓動電流 36A/230V
Cold-start current 36A/230V

漏電電流
Leakage current

<1mA/240VAC

過載保護
Over load protection

105~150% 切斷輸出,自動恢復
105~150% hiccup mode, auto-recovery

防水等級
Water level

IP68

啓動、上升、保持時間
Setup rise hold up time

200ms 100ms 20ms

耐壓性
Withstand voltage

I/P-O/P:1.5KvAC 1 minute
I/P-FG:1.5KvAC 1 minute
O/P-FG:0.5KvAC 1 minute

工作溫度、濕度
Working temperature

0~40°C@100%put
-10°C@80%put
50°C@60%put

重量/包裝
Weight/packing

0.65kg,30pcs/20kg

型號Type	輸出Output	差值Error	範圍range	效率Efficiency
FS-50-12	12V, 0~4.2A	±1%	100mV	78%
FS-50-15	15V, 0~2.1A	±1%	100mV	78%
FS-50-24	24V, 0~1.4A	±1%	100mV	82%