

# 60W LED防水型



- 接線:30cm綫材
- L, N: AC輸入
- -V黑: DC輸出負端
- +V紅: DC輸出正端

輸入電壓範圍 AC input voltage range	170~264VAC
輸入電流 Input current	1A/230V
衝擊電流 AC inrush current	冷啓動電流 36A/230V Cold-start current 36A/230V
漏電電流 Leakage current	<1mA/240VAC
過載保護 Over load protection	105~150% 切斷輸出,自動恢復 105~150% hiccup mode, auto-recovery
防水等級 Water level	IP68
啓動、上升、保持時間 Setup rise hold up time	200ms 100ms 20ms
耐壓性 Withstand voltage	I/P-O/P:1.5KvAC 1 minute I/P-FG:1.5KvAC 1 minute O/P-FG:0.5KvAC 1 minute
工作溫度、濕度 Working temperature	0~40°C @ 100% put -10°C @ 80% put 50°C @ 60% put
重量/包裝 Weight/packing	0.97kg,20pcs/20kg

型號Type	輸出Output	差值Error	範圍range	效率Efficiency
FS-60-12	12V, 0~5A	± 1%	120mV	76%
FS-60-15	15V, 0~2.5A	± 1%	150mV	77%
FS-60-24	24V, 0~1.7A	± 1%	150mV	79%
FS-60-48	48V, 0~1.2A	± 1%	150mV	81%