



CASE: P15-4 159×98×38mm

T-50系列三组输出

- 接线位置：7位 9.5mm端子
- L, N：AC输入 ■ +V2:DC输出正端
- ：接大地 ■ -V2:DC输出负端
- COM：DC输出公用地端
- +V1：DC输出正端

输入电压范围 AC input voltage range	85-132VAC/170-264VAC 47-63Hz 240-370VDC
输入电流 Input current	1.6A/115V 0.8A/230V
冲击电流 AC inrush current	冷启动电流 20A/115V 40A/230V Cold-start current 20A/115V 40A/230V
漏电流 Leakage current	<0.5mA/240VAC
直流电压可调范围 DC adjustable range	额定输出电压的±10% ±10% rated output voltage
过载保护 Over load protection	105-150% 切断输出, 自动恢复 105-150% hiccup mode, auto-recovery
过电压保护 Over-voltage protection	
启动、上升、保持时间 Setup rise hold up time	200ms 50ms 16ms
耐压性 Withstand voltage	I/P-O/P:3KVAC 1minute I/P-FG:1.5KVAC 1minute O/P-O/P:0.5KVAC 1minute
工作温度、湿度 Working temperature	-10℃~+60℃.20%-90% RH
重量/包装 Weight/packing	0.54kg.45pcs/24.3kg

型号type	输出Output	差值Error	范围Range	效率Efficiency
T-50A	5V,0.6-7A	±2%	100mV	66%
	12V,0.2-1A	±5%	100mV	
	-5V,0.2-1A	±5%	100mV	
T-50B	5V,0.6-5A	±2%	100mV	69%
	12V,0.2-1A	±5%	100mV	
	-12V,0.2-1A	±5%	100mV	
T-50C	5V,0.6-4A	±2%	100mV	71%
	15V,0.2-1A	±5%	100mV	
	-15V,0.2-1A	±5%	100mV	
T-50D	5V,0.6-4A	±2%	50mV	72%
	12V,0.2-1.2A	±6%	120mV	
	24V,0.2-1.2A	±6%	120mV	

